

ArChine Foodcare PAO 220**Food Grade, EP Gear/Bearing Lubricants****PRODUCT DESCRIPTION**

ArChine Foodcare PAO 220 is custom-blended polyalphaolefin (PAO) synthetic hydrocarbon fluids giving improved lubrication at high and low temperatures, reduced volatility, and compatibility with mineral oils and equipment designed for use with mineral oils.

ArChine Foodcare PAO 220 is long life lubricants formulated especially for applications where antiwear and extreme pressure properties are needed for effective load carrying ability. Recommended for gears and bearings.

Authorized by NSF for use in federally inspected meat and poultry plants (H-1).
Complies with FDA 21 CFR 178.3570 – lubricants with incidental food contact.

TYPICAL PROPERTIES*	220
Viscosity@40°C,cSt, ASTM D445	217.4
Viscosity @100°C,cSt	24.4
Viscosity Index ASTM D2270	141
Density lb/gal, 60°F	7.05
Pour point °C, ASTM D97	-43
Flash point C.O.C., °C, ASTM D92	307
Fire point C.O.C., °C, ASTM D92	307
Specific Gravity, ASTM D1298	0.846

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Adress: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.comE-mail: info@pingyiao.com