

CP-4722-30

PRODUCT DESCRIPTION

CP 4722-30 is a high quality synthetic alkylbenzene (AB) refrigeration lubricant. The lubricant is designed to be used with halogenated refrigerants in both refrigeration and air-conditioning applications. Years of experiences demonstrate that the CP 4722-30 is an excellent lubricant for systems using R-22, R-123 and R-502, particularly at low temperatures due to excellent miscibility characteristics.

Some advantages of using the CP 4722-30 over the traditional mineral oils are:

- Better Oil Return
- Better Thermal/Oxidation Stability
- Better System Efficiency
- Lower Foaming Tendency
- Lower Floc Point
- Excellent Miscibility

TYPICAL PROPERTIES*	CP-4722-30
Viscosity @ 40°C, cSt, ASTM D445	29.1
Viscosity @ 100°C, cSt	4.2
Viscosity @ 100°F, SUS	31.9
Viscosity @ 210°F, SUS	4.3
Viscosity Index ASTM D2270	-14
Gravity, 15°C	0.87
Pour Point °F (°C) ASTM D97	-43 (-45)
Flash Point, C.O.C., °F (°C) ASTM D92	347 (175)
Floc Point, °F (°C) ASHRAE-86	-58 (-73)
Dielectric Strength, KV D-877	45
Acid Number, mg/KOH/g	0.01
Miscibility with R-22, °F (°C)	-57 (-70)
Color, ASTM D 1500	0.5
Water Content (ppm)	20

Shanghai PingYiao Trading CO., Ltd.

Adress: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: www.pingyiao.com

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: info@pingyiao.com

Shanghai PingYiao Trading CO., Ltd.

Shanghai PingYiao Trading CO., Ltd.

Adress: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: www.pingyiao.com

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: info@pingyiao.com