

ArChine Syncomp PAO 46

PAO Synthetic Air Compressor Oil

Description

ArChine Syncomp PAO 46 is custom-blended polyalphaolefin(PAO) synthetic hydrocarbon fluid giving improved lubrication at high and low temperatures, reduced volatility, and compatibility with mineral oils and equipment designed for use with mineral oils.

Features

- Outstanding thermal oxidative stability
- Very low pour point
- Wide operating temperature range
- Reduced Maintenance and Downtime
- Extended drain intervals

Applications

- Rotary Screw Compressors
- Rotary Vane Compressors
- Centrifugal Compressors
- Reciprocating Compressors

Typical Physical Properties*

Properties	ArChine Syncomp PAO 46
Appearance	Light yellow clear liquid
Density@20°C, g/cm ³	0.836
Viscosity@ 40°C, mm ² /s	45.5
Viscosity@100°C, mm ² /s	7.43
Viscosity Index	127
Flash Point(open cup), °C	258

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Adress: A1207, Yin Hai Building, No.250, Caoxi Road, Xuhui District, Shanghai
200235 P.R.China

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com

ARCHINE

Shanghai PingYiao Trading CO., Ltd.

Fire Point, °C	278
Pour Point, °C	-51
Copper Strip Test, 100°C, 3hr	1
Foaming, 24°C	20/0

*The above data is typical data, not as product specifications.

Shanghai PingYiao Trading CO., Ltd.

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Adress: A1207, Yin Hai Building, No.250, Caoxi Road, Xuhui District, Shanghai
200235 P.R.China

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com