

CP-9331-46

PRODUCT DESCRIPTION

CP-9331-46 is a custom-blended semi-synthetic air compressor lubricant. The lubricant has excellent lubrication properties at both high and low temperatures, low volatility, superior chemical inertness. CP-9331-46 is designed for rotary screw applications. It is also compatible with mineral oils and equipment designed for use with both synthetic and mineral oils.

CP-9331-46 is non-toxic and carries no hazardous labels or warnings under the OSHA Right to Know Law 29 CFR 1910.1200.

TYPICAL PROPERTIES*	CP-9331-46
Viscosity @ 40°C, cSt, ASTM D445	47
Viscosity @ 100°C, cSt	7.0
Viscosity @ 100°F, SUS	240
Viscosity @ 210°F, SUS	50.1
Viscosity Index, ASTM D2270	100
Density, lb/gal, 60°F, ASTM D4052	7.2
Pour Point °F (°C), ASTM D97	0 (-18)
Flash Point, C.O.C., °F (°C), ASTM D92	440 (226)
Fire Point, C.O.C., °F (°C), ASTM D92	450 (232)
Specific Gravity, ASTM D4052	0.864

*These values are not intended for use in preparing specifications.

Shanghai PingYiao Trading CO., Ltd.

Address: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: www.pingyiao.com

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: info@pingyiao.com