

## **CP-1518-100-F (Wanner J, K oil)**

### **PRODUCT DESCRIPTION**

CP-1518-100-F product is a unique custom blend of polyalkylene glycols with additives for oxidation stability, corrosion protection, metal deactivators and lubricity. The compatibility of these products with EPDM makes them excellent lubricants in EPDM diaphragm pump applications. Other advantages include stability, low ash content, and high viscosity index, shear stability, low solubility with many hydrocarbons and excellent lubricity.

CP-1518-F series products comply with FDA 21 CFR 178.3510–Lubricants with Incidental Food Contact.

<b>TYPICAL PROPERTIES*</b>	<b>CP-1518-100-F</b>
Viscosity @ 40°C, cSt, ASTM D445	92.3
Viscosity @ 100°C, cSt	18.6
Viscosity @ 100°F, SUS	464
Viscosity @ 210°F, SUS	94.3
Viscosity Index, ASTM D2270	223
Density, lb/gal, 60°F, ASTM D4052	8.27
Pour Point °F (°C), ASTM D97	-40 (-40)
Flash Point, C.O.C., °F (°C), ASTM D92	500 (260)
Fire Point, C.O.C., °F (°C), ASTM D92	530 (277)
Specific Gravity, ASTM D4052	0.992

\*These values are not intended for use in preparing specifications.

Shanghai PingYiao Trading CO., Ltd.

Address: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: [www.pingyiao.com](http://www.pingyiao.com)

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: [info@pingyiao.com](mailto:info@pingyiao.com)