

# Shanghai PingYiao Trading CO., Ltd.

# **ArChine Comptek FPC 46**



## Food Grade Synthetic PAO Compressor Oil

## **Product Description**

ArChine Comptek FPC 46 is custom-blended with synthetic base fluids and special additives to provide excellent protection against wear and outstanding cold-temperature fluidity. It offers excellent performance in a wide range of temperatures including sub-zero temperatures. It also offers excellent water separation as well as rust, corrosion, deposit and water-washout resistance to protect components. In addition, it resists fling-off and is designed to remain on the chain for maximum lubrication and protection.

**ArChine Comptek FPC 46** is long life lubricant and recommended for use in screw compressors, evaporators and spiral freezers operating at extremely low temperatures including cryogenic-freezing temperatures.

**ArChine Comptek FPC 46** meets USDA H-1 requirements for incidental food contact and complies with requirements for FDA 21 CFR 178.3570.

### **Features and Benefits**

- Very high viscosity index for enhanced lubrication and superior protection at low temperatures
- Excellent film strength and anti-wear properties
- Outstanding cold-temperature fluidity
- Resists fling-off and remains on the chain for maximum lubrication and protection
- High stability and demulsibility in wet environments
- Excellent rust, corrosion and deposit resistance
- Non-toxic/non-hazardous

## **Applications**

| Primarily recommended for rotary screw and vane air compressor      |
|---|
| Very effective in screw type compressors with oil injection cooling |
| Units operating under severe conditions                             |

### **Distributor Wanted**

Shanghai PingYiao Trading CO., Ltd. Tel: 86-21-64705533 Adress: A1207, Yinhai Building, No.250, Caoxi Road, Xuhui District, Shanghai

200235 P.R.China

Telephone helpline: (86)15900706965 Fax: 86-21-64705533-209 Website: www.pingyiao.com E-mail: info@pingyiao.com



# Shanghai PingYiao Trading CO., Ltd.

- ☐ Multistage units with a history of excessive oil degradation from mineral oil-based products
- ☐ Compressor systems with critical gears and bearings
- ☐ Compressors used in stationary and mobile applications
- ☐ For spiral freezers operating at extremely low temperatures including cryogenic-freezing temperatures

## **Typical Properties\***

| ArChine Comptek FPC 46              | Typical Value                    |
|-------------------------------------|----------------------------------|
| Appearance                          | Light yellow, transparent liquid |
| Density@20°C, g/cm <sup>3</sup>     | 0.841                            |
| Viscosity@40°C, mm <sup>2</sup> /s  | 44.5                             |
| Viscosity@100°C, mm <sup>2</sup> /s | 7.39                             |
| Viscosity Index                     | 130                              |
| Flash Point, °C                     | 236                              |
| (open cup)                          | 230                              |
| Fire point, ℃                       | 262                              |
| Pour Point, °C                      | -48                              |
| Foaming,24°C,                       | 10/0                             |
| Copper corrosion,                   | 1                                |
| 100°C/3hr, grade                    | 1                                |

<sup>\*</sup>Typical data shall not be used as product specifications.

### **Distributor Wanted**

Shanghai PingYiao Trading CO., Ltd. Tel: 86-21-64705533 Adress: A1207, Yinhai Building, No.250, Caoxi Road, Xuhui District, Shanghai

200235 P.R.China

Telephone helpline: (86)15900706965 Fax: 86-21-64705533-209 Website: www.pingyiao.com E-mail: info@pingyiao.com