

ArChine Ammotech PAO 46

Polyalphaolefin ammonia refrigeration lubricant

Product Description

ArChine Ammotech PAO 46 is formulated with synthetic polyalphaolefin (PAO) base oils and a carefully balanced additive package developed for use in rotary screw compressors in refrigeration systems using ammonia. It has better oxidation resistance than conventional paraffinic and naphthenic-based refrigeration compressor oils, resulting in less buildup of varnish and sludge deposits and longer service life.

Features

- Excellent deposit control
- Rust and corrosion protection
- Resistance to foaming
- Outstanding thermal stability at high temperatures
- Lower volatility
- Lower oil consumption

Application

- Rotary screw refrigeration compressors using ammonia
- Ammonia manufacturing plants
- Ice plants

Typical Properties*

ArChine Ammotech PAO 46	Standard Specification
Appearance	Light yellow transparent liquid
Density@20°C, g/cm ³	0.831
Viscosity@40°C, mm ² /s	47.1
Viscosity@100°C, mm ² /s	7.61
Viscosity Index	128
Flash Point (open cup, °C)	250
Fire Point, °C	272

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Address: A1207, Yin Hai Building, No.250, Caoxi Road, Xuhui District, Shanghai
200235 P.R.China

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.comE-mail: info@pingyiao.com

ARCHINE

Shanghai PingYiao Trading CO., Ltd.

Pour Point, °C	-51
Foaming 24°C	20/0
Copper corrosion, 100°C/3hr,grade	1

*Typical data shall not be used as product specifications.

Shanghai PingYiao Trading CO., Ltd.

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Adress: A1207, Yin Hai Building, No.250, Caoxi Road, Xuhui District, Shanghai
200235 P.R.China

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com