

# CP-1516-220

## Hydrocarbon Gas Compressor Lubricant

### PRODUCT DESCRIPTION

CP-1516-220 product is unique custom blend of polyalkylene glycols with additives for oxidation stability, corrosion protection, metal deactivation and lubricity. The ability of CP-1516-220 lubricant to withstand dilution by hydrocarbon and other compressed gas is particularly advantageous in flooded screw compressors. Other advantages include stability, low ash content, high viscosity index, shear stability, and excellent lubricity.

### APPLICATIONS

Propane refrigeration compressor lubrication.

Natural gas and other light hydrocarbon compressor applications.

<b>TYPICAL PROPERTIES*</b>	<b>CP-1516-220</b>
Viscosity@40°C, cSt, ASTM D445	218.5
Viscosity@100°C, cSt	35.9
Viscosity@100°F	239.0
Viscosity@210°F	36.8
Viscosity Index ASTM D2270	214
Density, lb/gal, 60°F	8.32
Pour Point °F (°C)ASTM D97	-25(-32)
Flash Point, C.O.C., °F (°C)ASTM D92	500(260)
Fire Point, C.O.C., °F (°C)ASTM D92	550(288)
Specific Gravity, ASTM D1298	0.998

Shanghai PingYiao Trading CO., Ltd.

Adress: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: [www.pingyiao.com](http://www.pingyiao.com)

Tel: 86-21-64705533

Building, A1207 Room, No. 250

Fax: 86-21-64705533-209

E-mail: [info@pingyiao.com](mailto:info@pingyiao.com)