

ArChine Cotoo POE 130**Refrigeration Oil for CO₂ Compressors****PRODUCT DESCRIPTION**

ArChine Cotoo POE 130 is unique custom blend of synthetic Polyolester(POE) with additives for excellent wear protection, oxidation stability and lubricity. ArChine Cotoo POE 130 has an excellent solubility/miscibility with the refrigerant carbon dioxide (R 744).

ADVANTAGES

- High thermal stability
- High chemical stability with CO₂ refrigerant
- Excellent miscibility with CO₂ – also at low temperature
- Outstanding deep-temperature flowability
- Excellent lubrication at high pressure levels under CO₂ atmosphere

APPLICATIONS

ArChine Cotoo POE 130 is developed for use mainly in refrigeration systems which are working with the refrigerant CO₂ (R 744). ArChine Cotoo POE 130 has an excellent solubility/miscibility with CO₂ which guarantees the oil circulation in the refrigeration systems, especially at low evaporation temperatures.

TYPICAL PROPERTIES*

ArChine Cotoo POE 130	Standard Specification
Appearance	Light yellow clear liquid
Density, 20°C, g/cm ³	0.974
Kinematic Viscosity@40°C, mm ² /s	134.8
Kinematic Viscosity@100°C, mm ² /s	16.58
Viscosity Index	132

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Adress: A1207, Yin Hai Building, No.250, Caoxi Road, Xuhui District, Shanghai
200235 P.R.China

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.comE-mail: info@pingyiao.com

ARCHINE

Shanghai PingYiao Trading CO., Ltd.

Flash Point, Open Cup, °C	242
Fire Point, °C	262
Pour Point, °C	-42
Copper Corrosion, 100°C, 3h	1
Foaming 24°C	40/0
Acid Number, mg KOH/g	0.19
Water Content, mg/kg	205

*These values are not intended for use in preparing specifications.

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.

Adress: A1207, Yin Hai Building, No.250, Caoxi Road, Xuhui District, Shanghai
200235 P.R.China

Telephone helpline: (86)15900706965

Website: www.pingyiao.com

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: info@pingyiao.com