

CP-4700-75

Synthetic Refrigeration Fluid

PRODUCT DESCRIPTION

CP-4700-75 synthetic refrigeration fluid is alkylate based refrigeration oils. CP-4700-75 is friendly toward materials of construction, as well as exhibiting properties such as low floc points, and superior stability.

TYPICAL PROPERTIES*	CP-4700-75
Viscosity@40°C,cSt, ASTM D445	75.4
Viscosity@100°C,cSt	6.9
Viscosity@100°F	403.5
Viscosity@210°F	49.5
Viscosity Index ASTM D2270	5
Density,1b/gal, 60°F	7.20
Pour Point °F (°C) ASTM D97	-34(-30)
Flash Point,C.O.C., °F (°C) ASTM D92	390(199)
Fire Point, C.O.C., °F (°C) ASTM D92	405(207)
Specific Gravity, ASTM D1298	0.864
Floc Point°C, MAX, ASTM ASH86	< 5ml

*These values are not intended for use in preparing specifications.

Shanghai PingYiao Trading CO., Ltd.

Adress: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: www.pingyiao.com

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: info@pingyiao.com