

CP-4601-320

PRODUCT DESCRIPTION

CP-4601 Series are custom-blended polyalphaolefin (PAO) synthetic hydrocarbon fluids giving improved lubrication at high and low temperatures, reduced volatility, and compatibility with mineral oils and equipment designed for use with mineral oils.

CP-4601 Series (typical properties shown below) are long life lubricants formulated with rust and oxidation inhibitors. Other viscosities are available for specific applications.

CP-4601 Series are authorized by USDA for use in federally inspected meat and poultry plants with no possibility of food contact (H-2)

TYPICAL PROPERTIES*

CP-4601-320

Viscosity@40°C,cSt,ASTM D445	292.80
Viscosity @100°C,cSt	31.20
Viscosity @100°F	1522
Viscosity @210°F	152.2
Viscosity Index ASTM D2270	146
Density 1b/gal, 60°F	7.09
Pour point°F(°C) ASTM D97	-30(-34)
Flash point C.O.C.,°F(°C) ASTM D92	540(282)
Fire point C.O.C.,°F(°C) ASTM D92	560(293)
Specific Gravity, ASTM D1298	0.851

* These values are not intended for use in preparing specifications

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Address: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com