

Shanghai PingYiao Trading CO., Ltd.

ArChine Refritech XPE 170

Polyol Ester Refrigeration Compressor Fluid

Description

ArChine Refritech XPE 170 is proprietary blend of premium Polyol Ester technology base fluid and additives. This lubricant is formulated to provide superior protection for HFC refrigeration systems. ArChine Refritech XPE 170 offers exceptional solubility and superior lubricity in HFC and Blended Refrigerants.

ArChine Refritech XPE 170 has exceptional chemical and thermal stability, and offers a very long service life.

Benefits

- Excellent low temperature fluidity
- Optimized solubility
- Excellent film strength and anti-wear properties
- Very high flash point for added safety
- Enhanced carbon and varnish control to help reduce deposits
- Very low volatility
- Excellent corrosion and fust control
- Enhanced resistance against water contamination

Typical Properties

ArChine Refritech XPE	ISO 170
Appearance	Light yellow transparent liquid
Density@ 20°C, g/cm ³	0.978
Viscosity (cSt) @ 40°C	171.6
Viscosity (cSt) @ 100°C	18.6
Viscosity Index	122
Flash Point °C	282
Fire Point °C	304
Pour Point °C	-39
Copper Corrosion, 3 hr	1

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd. Tel: 86-21-64705533 Adress: A1207, Yinhai Building, No.250, Caoxi Road, Xuhui District, Shanghai

200235 P.R.China

Telephone helpline: (86)15900706965 Fax: 86-21-64705533-209 Website: www.pingyiao.com E-mail: info@pingyiao.com



Shanghai PingYiao Trading CO., Ltd.

Foam Characteristic, 24°C 25/0

Shanahai Pina Yiao Tradinas

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd. Tel: 86-21-64705533 Adress: A1207, Yinhai Building, No.250, Caoxi Road, Xuhui District, Shanghai

200235 P.R.China

Telephone helpline: (86)15900706965 Fax: 86-21-64705533-209 Website: www.pingyiao.com E-mail: info@pingyiao.com

^{*} The above data is typical data, not as product specifications.