

ArChine Screwtech PME 32**12000 hours Screw Air Compressor Oil****Description**

ArChine Screwtech PME 32 is premium screw compressor lubricant using advanced technology additives custom-blended with synthetic hydrocarbon and polyol ester fluids. It has a service life expectancy of 12000 hours with proper maintenance and sampling.

Features

- Improved performance at higher temperatures
- Lower volatility
- Excellent oxidative stability and thermal stability
- Improved resistance to sludge and varnish formation
- Good heat transfer and cooler efficiency

Applications

- Screw air compressors
- Not compatible with low nitrile Buna, acrylic paint, polystyrene, PVC or ABS

Typical Physical Properties*

Properties	ArChine Screwtech PME 32
Appearance	Light yellow clear liquid
Density@20°C, g/cm ³	0.883
Viscosity@ 40°C, mm ² /s	30.4
Viscosity@100°C, mm ² /s	5.52
Viscosity Index	120
Flash Point(open cup), °C	246
Fire Point, °C	268
Pour Point, °C	-57

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Address: A1207, Yin Hai Building, No.250, Caoxi Road, Xuhui District, Shanghai
200235 P.R.China

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.comE-mail: info@pingyiao.com

ARCHINE

Shanghai PingYiao Trading CO., Ltd.

Copper Strip Test, 100°C, 3hr	1
Foaming, 24°C	15/0

*The above data is typical data, not as product specifications.

Shanghai PingYiao Trading CO., Ltd.

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Adress: A1207, Yin Hai Building, No.250, Caoxi Road, Xuhui District, Shanghai
200235 P.R.China

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com