

ArChine Semicomp HVI 46**Semi-Synthetic Screw Air Compressor Oil****Description**

ArChine Semicomp HVI 46 is formulated from highly refined “semi-synthetic”, hydrocracked base stocks and unique additives. It is designed for rotary screw compressors.

Features

- Extended 4000-5000 hour typical life
- Thermal and hydrolytic stability
- Very low water content for maximum bearing life
- Low volatility

Application

These high-performance lubricants are recommended for use in:

Flooded rotary screw air compressors

Centrifugal air compressor: service life: 16000 hours

Typical Physical Properties*

Properties	ArChine Semicomp HVI 46
Appearance	Light yellow clear liquid
Density@20°C, g/cm ³	0.863
Viscosity@ 40°C, mm ² /s	44.5
Viscosity@100°C, mm ² /s	6.98
Viscosity Index	114
Flash Point(open cup), °C	230
Fire Point, °C	250
Pour Point, °C	-39
Copper Strip Test, 100°C, 3hr	1

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Adress: A1207, Yin Hai Building, No.250, Caoxi Road, Xuhui District, Shanghai
200235 P.R.China

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com

ARCHINE

Shanghai PingYiao Trading CO., Ltd.

Foaming, 24°C	10/0
---------------	------

*The above data is typical data, not as product specifications.

Shanghai PingYiao Trading CO., Ltd.

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Adress: A1207, Yin Hai Building, No.250, Caoxi Road, Xuhui District, Shanghai
200235 P.R.China

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com