

ArChine Foodcare FMO 460 Food Grade Gear Lubricants

PRODUCT DESCRIPTION

ArChine Foodcare FMO 460 is custom-blended highly refined, chemically inert lubricants with additives for improved lubricity and defoaming characteristics. Widely used for applications in the food processing industries where the lubricant has indirect contact with food substances. ç, 00

APPLICATIONS

- Energy saving gear application;
- Lubricant for vacuum pumps;
- General purpose lubricant for long life and antiwear;
- Lubricant/coolant for compressors;

- Lubricant and sealing fluid for rotary mechanical shaft seals of processing pumps and agitated kettles.

TYPICAL PROPERTIES	460
Viscosity@40°C,cSt,ASTM D445	401.6
Viscosity@100°C,cSt	31
Viscosity indexASTM D2270	110
Density, lb/gal,60°C	7.3
Pour point (°C)	-21
Flash point C.O.C., (°C) ASTM D92	254
Fire point C.O.C., (°C) ASTM D92	277
Specific Gravity, ASTM D1298	0.88

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd. Tel: 86-21-64705533 Adress: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250 Telephone helpline: (86)15900706965 Fax: 86-21-64705533-209 Website: www.pingyiao.com E-mail: info@pingyiao.com