

ArChine Syncomp POE 150**POE Synthetic Air Compressor Oil****Description**

ArChine Syncomp POE 150 is custom-blended polyol ester (POE) synthetic lubricant. It is long life lubricant offering thermal oxidative resistance and lubricity. This product is especially advantageous in high temperature applications and do not leave varnish or sludge residue as often happens with mineral oil based products.

Features

- Outstanding low and high temperature properties
- Excellent corrosion protection
- Excellent oxidative stability and thermal stability
- No deposit or varnish formation
- Superior demulsibility

Applications

- Oil flooded rotary vane compressors
- Axial and centrifugal compressor
- Wide variety of hydraulic, gear and bearing and compressor applications

Typical Physical Properties*

Properties	ArChine Syncomp POE 150
Appearance	Yellow clear liquid
Density@20°C, g/cm ³	0.980
Viscosity@ 40°C, mm ² /s	156.5
Viscosity@100°C, mm ² /s	16.31
Viscosity Index	110
Flash Point(open cup), °C	286
Fire Point, °C	308

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Adress: A1207, Yin Hai Building, No.250, Caoxi Road,Xuhui District , Shanghai
200235 P.R.China

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.comE-mail: info@pingyiao.com

ARCHINE

Shanghai PingYiao Trading CO., Ltd.

Pour Point, °C	-39
Copper Strip Test, 100°C, 3hr	1
Foaming, 24°C	25/0

*The above data is typical data, not as product specifications.

Shanghai PingYiao Trading CO., Ltd.

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Adress: A1207, Yin Hai Building, No.250, Caoxi Road, Xuhui District, Shanghai
200235 P.R.China

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com