

**ArChine Refritech QPE 220 (POE 220)**

ArChine Refritech QPE 220 (POE 220) is designed for standard factory fill of air conditioning and industrial refrigeration equipment, as well as for OEM retrofitting operations. It provides improved properties over conventional mineral oils in all aspects, including viscosity index, flash and fire points, and pour point.

Through this effort, we've been able to identify lubricants that meet a compressor's specific requirements and needs.

<b>ArChine Refritech QPE</b>	<b>ISO 220</b>
Appearance	Light yellow transparent liquid
Density@ 20°C, g/cm <sup>3</sup>	0.963
Viscosity (cSt) @ 40°C	228.34
Viscosity (cSt) @ 100°C	18.98
Viscosity Index	93
Flash Point °C	292
Fire Point °C	318
Pour Point °C	-24
Copper Corrosion, 3 hr	1
Foam Characteristic, 24°C	35/0

\* The above data is typical data, not as product specifications.ies.

**Distributor Wanted**

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Adress: A1207, Yin Hai Building, No.250, Caoxi Road, Xuhui District, Shanghai  
200235 P.R.China

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: [www.pingyiao.com](http://www.pingyiao.com)

E-mail: [info@pingyiao.com](mailto:info@pingyiao.com)