

Shanghai PingYiao Trading CO., Ltd.

ArChine Syncomp POE 32

POE Synthetic Air Compressor Oil

Description

ArChine Syncomp POE 32 is custom-blended polyol ester (POE) synthetic lubricant. It is long life lubricant offering thermal oxidative resistance and lubricity. This product is especially advantageous in high temperature applications and does not leave varnish or sludge residue as often happens with mineral oil based products.

Features

- Outstanding low and high temperature properties
- Excellent corrosion protection
- Excellent oxidative stability and thermal stability
- No deposit or varnish formation
- Superior demulsibility

Applications

- Oil flooded rotary vane compressors
- Axial and centrifugal compressor
- Wide variety of hydraulic, gear and bearing and compressor applications

Typical Physical Properties*

Properties	ArChine Syncomp POE 32
Appearance	Yellow clear liquid
Density@20°C, g/cm ³	0.950
Viscosity@ 40°C, mm ² /s	30.0
Viscosity@100°C, mm²/s	5.46
Viscosity Index	119
Flash Point(open cup), °C	248
Fire Point, °C	272

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd. Tel: 86-21-64705533 Adress: A1207, Yinhai Building, No.250, Caoxi Road, Xuhui District, Shanghai

200235 P.R.China

Telephone helpline: (86)15900706965 Fax: 86-21-64705533-209 Website: www.pingyiao.com E-mail: info@pingyiao.com



Shanghai PingYiao Trading CO., Ltd.

Pour Point, ℃	-39
Copper Strip Test, 100°C, 3hr	1
Foaming, 24°C	15/0

^{*}The above data is typical data, not as product specifications.

Shanahai Pina Yiao Fradinas

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd. Tel: 86-21-64705533 Adress: A1207, Yinhai Building, No.250, Caoxi Road, Xuhui District, Shanghai

200235 P.R.China

Telephone helpline: (86)15900706965 Fax: 86-21-64705533-209 Website: www.pingyiao.com E-mail: info@pingyiao.com