

## **CP-4126-220**

### **PRODUCT DESCRIPTION**

CP-4126-220 is a diester based synthetic lubricants specially formulated for rotary vane or reciprocating air compressor applications. Benefits of using these lubricants include:

- Eliminate the formation of sludge, varnish and other deposits
- Extended lubricant life
- Superior demulsibility
- Wide operating temperature range

<b>TYPICAL PROPERTIES*</b>	<b>CP-4126-220</b>
Viscosity @ 40°C, cSt, ASTM D445	222.08
Viscosity @ 100°C, cSt	18.52
Viscosity @ 100°F, SUS	1185
Viscosity @ 210°F, SUS	94.7
Viscosity Index, ASTM D2270	92
Density, lb/gal, 60°F, ASTM D4052	7.76
Pour Point °F(°C), ASTM D97	-27.4(-33)
Flash Point, C.O.C., °F(°C), ASTM D92	470(243)
Fire Point, C.O.C., °F(°C), ASTM D92	505(263)
Specific Gravity, ASTM D4052	0.931

\*These values are not intended for use in preparing specifications.

Shanghai PingYiao Trading CO., Ltd.

Address: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: [www.pingyiao.com](http://www.pingyiao.com)

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: [info@pingyiao.com](mailto:info@pingyiao.com)