

CP-1516-85

Hydrocarbon Gas Compressor Lubricant

PRODUCT DESCRIPTION

CP-1516-85 product is unique custom blend of polyalkylene glycols with additives for oxidation stability, corrosion protection, metal deactivation and lubricity. The ability of CP-1516-85 lubricant to withstand dilution by hydrocarbon and other compressed gas is particularly advantageous in flooded screw compressors. Other advantages include stability, low ash content, high viscosity index, shear stability, and excellent lubricity.

APPLICATIONS

Propane refrigeration compressor lubrication.

Natural gas and other light hydrocarbon compressor applications.

TYPICAL PROPERTIES*	CP-1516-85
Viscosity@40°C,cSt, ASTM D445	85.0
Viscosity@100°C,cSt	12.0
Viscosity@100°F	94.2
Viscosity@210°F	12.3
Viscosity Index ASTM D2270	137
Density, lb/gal, 60°F	8.26
Pour Point °F (°C)ASTM D97	-36(-33)
Flash Point, C.O.C., °F (°C)ASTM D92	560(293)
Fire Point, C.O.C., °F (°C)ASTM D92	590(310)
Specific Gravity, ASTM D1298	0.991

Shanghai PingYiao Trading CO., Ltd.

Adress: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: www.pingyiao.com

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: info@pingyiao.com